



特点:

- 支持 Intel® 12/13th Generation Core/Pentium/Celeron Desktop CPU
- 全套模具成型, 标准 19 英寸 2U 上架式机箱
- 安装标准 ATX 主板, 支持标准 2U 电源
- 最多支持 7 槽位半高卡扩展, 满足多行业应用需求
- 人性化设计, 机箱前置系统风扇免工具维护
- 最多可选 4 个 3.5 英寸抗震抗冲击硬盘位
- 前面板 USB、开关机设计, 电源及存储状态显示, 更易于系统维护



远程管理



状态监控



远程运维




安全控制


产品规格

Model	IPC200-Q670	
Processor System	CPU	Support Intel® 12/13th Generation Core / Pentium/ Celeron Desktop CPU
	TDP	125W
	Socket	LGA1700
	Chipset	Q670
	BIOS	AMI 256 Mbit SPI
Memory	Socket	4 * Non-ECC U-DIMM Slot, Dual Channel DDR4 up to 3200MHz
	Capacity	128GB, Single Max. 32GB
Graphics	Controller	Intel® UHD Graphics
Ethernet	Controller	1 * Intel i225-V/LM 2.5GbE LAN Chip (10/100/1000/2500 Mbps, RJ45) 1 * Intel i219-LM/V GbE LAN Chip (10/100/1000 Mbps, RJ45)
Storage	SATA	4 * SATA3.0 7P Connector, Support RAID 0, 1, 5, 10
	M.2	1 * M.2 Key-M (PCIe x4 Gen 4 + SATA3.0, NVMe/SATA SSD Auto Detect, 2242/2260/2280)
Expansion Slots	PCIe	2 * PCIe x16 slot (Gen 5, x16 /NA signal or Gen 4, x8 /x8 signal)
		1 * PCIe x8 slot (Gen 4, x4 signal)
		2 * PCIe x4 slot (Gen 4, x4 signal)
		1 * PCIe x4 slot (Gen 3, x4 signal)
	PCI	1 * PCI slot
Mini PCIe	1 * Mini PCIe (PCIe x1 Gen 3 + USB 2.0, with 1 * SIM Card)	
M.2	1 * M.2 Key-B (USB3.2 Gen 1x1 (co-lay with usb header, default), with 1 * SIM Card, 3042/3052)	
Front I/O	Ethernet	2 * RJ45
	USB	4 * USB3.2 Gen 2x1 (Type-A)
		4 * USB3.2 Gen 1x1 (Type-A)
	Display	1 * DP1.4: max resolution up to 3840*2160 @ 60Hz
		1 * HDMI2.0: max resolution up to 3840*2160 @ 30Hz
	Audio	3 * 3.5mm Jack (Line-out + Line-in + MIC)
Serial	2 * RS232/422/485 (COM1/2, DB9/M, Full Lanes, BIOS Switch)	
Rear I/O	USB	2 * USB2.0 (Type-A)
	Button	1 * Power Button
	LED	1 * Power status LED 1 * Hard drive status LED
Internal I/O	USB	1 * USB3.2 Gen 1x1 (Vertical TYEP-A) 2 * USB2.0 (One of four shares a signal with the M.2 Key-B, optional, Header)
	COM	4 * RS232 (COM3/4/5/6, Header, Full Lanes)
	Display	1 * VGA: max resolution up to 1920*1200 @ 60Hz (wafer)
		1 * eDP: max resolution up to 1920*1200 @ 60Hz (Header)
	Audio	1 * Front Audio (Line-Out + MIC, Header)
		1 * Speaker (3W (per channel) into a 4Ω Loads, wafer)
	GPIO	1 * 16 bits DIO (8DI and 8DO, wafer)
	SATA	4 * SATA 7P Connector
	LPT	1 * LPT (Header)
	PS/2	1 * PS/2 (wafer)
	SMBus	1 * SMBus (wafer)
FAN	2 * SYS FAN (Header)	
	1 * CPU FAN (Header)	
Power Supply	Type	2U FLEX
	Power Input Voltage	AC power supply, voltage and frequency shall be based on the 2U power supply provided
	RTC Battery	CR2032 Coin Cell
OS Support	Windows	Windows 10/11
	Linux	Linux
Watchdog	Output	System Reset
	Interval	Programmable 1 ~ 255 sec
Mechanical	Enclosure Material	SGCC+AL6061
	Dimensions	482.6mm(L) * 475.7mm(W) * 88.1mm(H)
	Mounting	Rack-mounted/Desktop
Environment	Operating Temperature	0 ~ 50°C
	Storage Temperature	-20 ~ 70°C
	Relative Humidity	10 to 95% RH (non-condensing)

产品尺寸



机箱接口



主板接口

