



特点:

- 全屏电阻触摸屏设计
- 模块化设计 12.1~21.5"可选,支持方屏/宽屏
- 前面板满足 IP65 要求
- 前面板集成 USB Type-A 和信号指示灯
- 支持 Intel® 12/13th Gen Core / Pentium/ Celeron Desktop CPU, TDP 65W, LGA1700
- 搭配 Intel® H610 芯片组
- 2 个 Intel 网络接口 (1*1GbE & 1*2.5GbE)
- 3 路显示输出 HDMI, DP++和内部 LVDS, 最高支持 4K@60Hz 分辨率
- 丰富的 USB、串口扩展接口和 PCIe、mini PCIe、M.2 扩展插槽
- 智能风扇主动散热



远程管理



状态监控



远程运维



安全控制

产品规格

Model	PL121RQ-E7S	PL150RQ-E7S	PL156RQ-E7S	P170RQ-E7S	PL185RQ-E7S	PL191RQ-E7S	PL215RQ-E7S	
LCD	Display Size	12.1"	15.0"	15.6"	17.0"	18.5"	19.1"	21.5"
	Display Type	XGA TFT-LCD	XGA TFT-LCD	FHD TFT-LCD	SXGA TFT-LCD	WXGA TFT-LCD	WXGA TFT-LCD	FHD TFT-LCD
	Max.Resolution	1024 x 768	1024 x 768	1920 x 1080	1280 x 1024	1366 x 768	1440 x 900	1920 x 1080
	Luminance	350 cd/m2	300 cd/m2	350 cd/m2	250 cd/m2	250 cd/m2	250 cd/m2	250 cd/m2
	Aspect Ratio	4:3	4:3	16:9	5:4	16:9	16:10	16:9
	Viewing Angle	80/80/80/80°	88/88/88/88°	89/89/89/89°	85/85/80/80°	89/89/89/89°	85/85/80/80°	89/89/89/89°
	Max. Color	16.7M	16.7M	16.7M	16.7M	16.7M	16.7M	16.7M
	Backlight Lifetime	30,000 hr	70,000 hr	50,000 hr	30,000 hr	30,000 hr	30,000 hr	50,000 hr
Touchscreen	Contrast Ratio	800:1	2000:1	800:1	1000:1	1000:1	1000:1	1000:1
	Touch Type	5-wire resistive touch	5-wire resistive touch	5-wire resistive touch	5-wire resistive touch	5-wire resistive touch	5-wire resistive touch	5-wire resistive touch
	Controller	USB signal	USB signal	USB signal	USB signal	USB signal	USB signal	USB signal
	Input	finger/touch pen	finger/touch pen	finger/touch pen	finger/touch pen	finger/touch pen	finger/touch pen	finger/touch pen
	Light Transmission	≥78%	≥78%	≥78%	≥78%	≥78%	≥78%	≥78%
Processor System	Hardness	≥3H	≥3H	≥3H	≥3H	≥3H	≥3H	≥3H
	CPU	Intel® 12/13th Generation Core / Pentium/ Celeron Desktop CPU						
	TDP	65W						
	Socket	LGA1700						
	Chipset	H610						
Memory	BIOS	AMI 256 Mbit SPI						
	Socket	2 * Non-ECC SO-DIMM Slot, Dual Channel DDR4 up to 3200MHz						
Graphics	Max Capacity	64GB, Single Max. 32GB						
	Controller	Intel® UHD Graphics						
Ethernet	1 * Intel i219-LM 1GbE LAN Chip (LAN1, 10/100/1000 Mbps, RJ45)							
	1 * Intel i225-V 2.5GbE LAN Chip (LAN2, 10/100/1000/2500 Mbps, RJ45)							
Storage	SATA	1 * SATA3.0, Quick release 2.5" hard disk bays (T ≤ 7mm)						
	M.2	1 * M.2 Key-M (SATA3.0, 2280)						
Expansion Slots	aDoor	1 * aDoor Bus (Optional 4 * LAN/4 * POE/6 * COM/16 * GPIO expansion card)						
	Mini PCIe	1 * Mini PCIe (PCIe3.0 x1 + USB 2.0, with 1*Nano SIM Card)						
Front I/O	Ethernet	2 * RJ45						
	USB	2 * USB3.2 Gen2x1(Type-A, 10Gbps) 2 * USB3.2 Gen1x1(Type-A, 5Gbps) 2 * USB2.0 (Type-A)						
	Display	1 * HDMI1.4b: max resolution up to 4096*2160 @ 30Hz 1 * DP1.4a: max resolution up to 4096*2160 @ 60Hz						
	Audio	2 * 3.5mm Jack (Line-Out + MIC)						
	Serial	2 * RS232/485/422 (COM1/2, DB9/M, Full Lanes, BIOS Switch) 2 * RS232 (COM3/4, DB9/M, Full Lanes)						
	Button	1 * Power Button + Power LED 1 * AT/ATX Button 1 * OS Recover Button 1 * System Reset Button						
Rear I/O	Antenna	4 * Antenna hole						
	SIM	1 * Nano SIM card slots(SIM1)						
Internal I/O	USB	6 * USB2.0 (wafer)						
	LCD	1 * LVDS (wafer): LVDS Resolution up to 1920*1200 @ 60Hz						
	Front Panel	1 * FPanel (PWR+RST+LED, wafer)						
	Audio	1 * Audio (Header) 1 * Speaker (2-W (per channel)/8-Ω Loads, wafer)						
	Serial	2 * RS232 (COM5/6, wafer)						
	GPIO	1 * 16 bits DIO (8xDI and 8xDO, wafer)						
	LPC	1 * LPC (wafer)						
	SATA	3 * SATA 7P Connector, up to 600MB/s						
	SATA Power	3 * SATA Power (wafer)						
	FAN	1 * CPU FAN (wafer) 2 * SYS FAN (KF2510-4A)						
Power Supply	Type	DC, AT/ATX						
	Power Input Voltage	9~36VDC, P ≤ 240W 18~60VDC, P ≤ 400W						
	Connector	1 * 4Pin Connector, P=5.00/5.08						
	RTC Battery	CR2032 Coin Cell						
OS Support	Windows	Windows 10/11						
	Linux	Linux						
Watchdog	Output	System Reset						
	Interval	Programmable 1 ~ 255 sec						

Mechanical	Enclosure Material	Radiator: Aluminum alloy, Box: SGCC						
	Mounting	VESA, Embedded						
	Dimensions (L * W * H, Unit: mm)	321.9*260.5*95.7	380.1*304.1*95.7	420.3*269.7*95.7	414*346.5*95.7	485.7*306.3*95.7	484.6*332.5*95.7	550*344*95.7
Environment	Weight	Net: 6.66Kg Total: 8.16Kg	Net: 8.05Kg Total: 9.55Kg	Net: 7.95Kg Total: 9.45Kg	Net: 8.8Kg Total: 10.6Kg	Net: 8.65Kg Total: 10.45Kg	Net: 10.05Kg Total: 11.85Kg	Net: 9.58Kg Total: 11.38Kg
	Heat Dissipation System	PWM Fan Cooling						
	Operating Temperature	-20~60°C	-20~60°C	-20~60°C	-20~60°C	-20~60°C	0~50°C	0~50°C
	Storage Temperature	-20~60°C	-20~70°C	-30~80°C	-30~70°C	-30~70°C	-20~60°C	-20~60°C
	Relative Humidity	10 to 95% RH (non-condensing)						
	Vibration During Operation	With SSD: IEC 60068-2-64 (1Grms@5~500Hz, random, 1hr/axis)						
	Shock During Operation	With SSD: IEC 60068-2-27 (15G, half sine, 11ms)						
Certification	CE/FCC, RoHS							

产品尺寸

A	System Dimension			Panel Mount							
	X1	Y1	Z1	X2	Y2	Z2	X3	Y3	Z3	F1	F2
12.1"	321.9	260.5	95.7	307	245.6	28	309.8	248.4	8	7.1	8.5
15.0"	380.1	304.1	95.7	364.2	288.2	28	367	291	8	7.1	8.5
15.6"	420.3	269.7	95.7	404.5	253.8	28	407.3	256.6	8	7.1	8.5
17.0"	414	346.5	95.7	398.2	330.6	28	401	333.4	8	7.1	8.5
18.5"	485.7	306.3	95.7	469.8	290.4	28	472.6	293.2	8	7.1	8.5
19.1"	484.6	332.5	95.7	468.7	316.6	28	471.5	319.4	8	7.1	8.5
21.5"	550	344	95.7	538.7	327.7	28	539.5	330.9	8	7.1	8.5

产品 I/O

AR/aDoor Expansion I/O GND USB3.2*4 DC IN LAN*2 DP USB2.0*2 HDMI Audio COM4/3 Reset/ OS REC ATX/AT COM2/1 PWR/LED 2.5" Disk

Nano SIM(Only support SIM1)

CPU FAN